



# Our maintenance advice for Elegance and Emotion decking boards







Emotion board



It is essential to wash your decking once a year, ideally in spring, using a long-handled broom and hot soapy water for optimum effectiveness.

A second wash in the autumn/at the end of the season is also recommended to reduce the amount of dirt and make it easier to clean in the spring.



Scatter a sodium-bicarbonatebased laundry detergent powder (e.g. "Le Chat Expert®") on the boards, wet the cleaning tool with warm water, rub the

surface, leave to work and rinse

with plenty of water.



**IMPORTANT:** Have you remembered to clean between the boards? Dirt can build up over time, which can lead to moisture retention and reduce ventilation on the decking. We recommend using a flexible material (such as a plastic or wooden ruler).

We recommend using a Kärcher 40/10 C type scrubber-drier or equivalent without a high-pressure jet for effective cleaning of large surfaces. There are various types of brush available for use with this machine:



### > Smooth Elegance, Embossed Elegance and Emotion boards

We recommend using a conventional brush (green) for a basic spring cleaning or for routine maintenance.



Note: There are brushes available featuring scraping fibre discs for more aggressive cleaning. We recommend testing them on a small area beforehand, as they will abrade the surface of the boards. **CAUTION** the wood grain of the embossed board may fade: these brushes are not compatible with Atmosphere boards either.



## > Grooved Elegance board

A brush (orange) with two bristle heights is particularly suitable for grooved boards.





For borders and smaller decking areas, a more basic model such as the Kärcher PCL4 or equivalent is sufficient.

These types of scrubber-drier **do not operate with a high-pressure jet**, but with brushes that inject clean water (with or without soap) in a single pass, effectively scrubbing the decking. They clean the boards, removes green deposits and bird droppings, and reduces surface scratches.

They can be used all year round, without chemicals, so there's no risk to the environment or the materials around you.

#### > OUR RECOMMENDATIONS FOR USE

Model	Estimated performance	Comments
Long-handled broom	10m²/hour with 1 person	requires elbow grease
PCL4 or equivalent	15 m²/hour with 1 person and 1 machine	There is only one type of brush, which should be tested in an inconspicuous area beforehand.
40/10C or equivalent	40 m²/hour with 1 person and 1 machine	Setting: position 2 Several brush options









e-mail: info-germany@silvadec.com

#### Action(s) to take Type of mark Cause It is advisable to take action immediately after the stain appears, with our Silvawash stain remover. For stubborn stains, use an aliphatic Mainly food hydrocarbons-based stain remover (e.g. Starwax®) suitable for composite **GREASE** stains: products, and apply on top of the Silvawash powder for ~12 hrs. This STAINS barbecue, oil, treatment may slightly lighten the board, but the colour will become more ice cream, etc. uniform with time. Refer to the product instructions for use and follow the safety precautions. Caused by **STUBBORN** Clean by hand with a long-handled broom or a sponge with a scraper, and atmospheric **DIRT STAINS,** hot soapy water. For larger surfaces, a scrubber-drier can also be used. If pollution, the dirt **BLACK DRIPS** the stain persists, use our **Silvanet** product, following the method shown is deposited on ON FENCING on the bottle, and rinse with plenty of water. the surface. A scratched surface can be sanded to eliminate the scratch. The area will be a slightly lighter shade after sanding, but this colour difference will Gravel, sharp **SCRATCHES** disappear after UV/weather exposure. This method is unsuitable for objects, etc. embossed boards (sanding removes the wood grain pattern on the surface). Inadequate **ALL BOARDS:** maintenance Use Silvaction. If you use an antifoaming product (without bleach), of the boards MOSS / test the product on an inconspicuous area before use. creates an **LICHEN** environment In all cases, refer to the product's instruction for use and following the

#### > CLEANING PRODUCTS



#### **SILVAWASH**

· Clay-based, 100% mineral origin

very conducive to

moss developing

- Especially for composite
- · To be used dry
- · Net weight: 200g

Ref. SINET1501



safety precautions.

#### **SILVACTION**

- · Ready for use, without rinsing
- Capacity: 5 I (20/25 m<sup>2</sup>)
- Ideal for heavy one-off "scrubbing" actions

Ref. SINET1801



#### **SILVANET**

- · Especially for composites
- Removes ground-in stains

Ref. SINET1201

#### THINGS YOU SHOULD NEVER DO

- · Do not use high-pressure cleaning equipment, which makes the surface slightly porous and so more prone to staining
- Do not use solvent
- Do not apply staining oil, paint or protective/restorer products.







#### > TEMPORARY BRONZING OF THE BOARDS

Composite boards are mostly made of wood and are therefore liable to staining, dependent on the product's environment, its use and your regional climate. Stains are always on the surface of the board and never alter the structure of the product. Most of them can be easily cleaned off. Household stains (greasy stains) fade naturally if they are exposed frequently to UV and the weather. These boards yellow temporarily during the first few weeks after installation.





This natural phenomenon disappears after exposure to the sun and to the weather, at which point the boards will revert to almost their original colour! This bronzing may last longer if the boards are installed in semisheltered or sheltered areas. In this case, if water spots persist, it is possible to speed up their disappearance by using a jet of water and a long-handled broom to brush along the length of the boards.







